5

3

7

9

10

12

11

13 14

15

16

17

18 19

20

21

22

23

Listing of Claims

- 1. (Currently Amended) A constant height An adjustable line trimmer, comprising:
- a line trimmer including a main pole, a handle attached to one end of said main pole, and a trimmer head attached to the end of the main pole opposite said handle, said trimmer head including a rotating line capable of cutting vegetation;
 - b. a short straight extension arm having a distal end and a proximal end;
- a wheel assembly attached to said distal end of said extension arm, said wheel c. assembly including at least one wheel rotatably mounted thereon; and,
- d. a first clamp member used to longitudinally align and attach said extension arm to said main pole on said line trimmer so that said distal end of said extension arm extends forward from the trimmer head, said first clamp member able to move longitudinally over said main pole thereby allowing said wheel assembly to be positioned in front of said trimmer head at different distances to support said trimmer head at different desired angles and elevations above a support surface when said handle is held and said line trimmer is pushed or pulled over a support surface; and,
- a second clamp member attached to said extension arm that enables the length of said extension pole between said first clamp member and said wheel assembly to be adjusted thereby allowing the pitch of said extension arm relative to the main pole to be adjusted.

2. (Previously Amended) The line trimmer, as recited in Claim 1, further including said wheel assembly being rotatably attached to said distal end of said extension arm and a locking means for selectively locking said wheel assembly in a desired position on said

1	extension arm.
2	
3	3. (Cancelled)
4	
5	4. (Currently Amended) The line trimmer, as recited in Claim 3 1, further including said
6	wheel assembly being rotatably attached to said distal end of said extension arm and a
7	locking means for selectively locking said wheel assembly in a desired position on said
8	extension arm.
9	
10	5. (Currently Amended) The line trimmer, as recited in Claim 3 1, wherein said first and
11	second clamp members are formed on a rotating L-shaped bracket selectively attaching said
12	extension arm to the main pole, said L-shaped bracket includes a first support flange that
13	supports said first clamp member and a second support flange that supports said second
14	clamp member, said first support flange and said second support flange being perpendicularly
15	aligned thereby perpendicularly aligning said first clamp member and said second clamp
16	member <u>.</u>
17	
18	6. (Previously Amended) The line trimmer, as recited in Claim 5, further including said
19	wheel assembly being rotably attached to said distal end of said extension arm and a locking
20	means enabling said wheel assembly to be selectively locked in a desired position on said
21	extension arm.
22	
23	7. (Previously Amended) The line trimmer as recited in Claim 1, wherein said first clamp

23

member includes an upper clamp member, a lower clamp member, a center post, a pivoting handle attached to said post, and a strap, said upper and lower clamp members including teeth that selectively engage when said upper and lower clamp members are forced together, said strap member extending through said lower clamp member and wrapped around a main pole on a line trimmer, said center post extending through said upper clamp member and connecting to said strap to connect said upper clamp member and said lower clamp member together and to tighten said strap around the main pole.

- 8. (Currently Amended) An accessory for a line trimmer that includes a main pole with a trimmer head attached at one end, said accessory comprising:
 - a short straight extension arm having a distal end and a proximal end;
- b. a wheel assembly attached to said distal end of said extension arm, said wheel assembly including at least one wheel mounted thereon;
- c. an adjustable first clamp member attached to said proximal end of said extension arm, said first clamp member capable of being selectively attached to a main pole on a line trimmer to connect said extension arm to the main pole, said first clamp member being adjustable along said extension arm so that the distance between of said wheel assembly and a trimmer head attached to the main pole may be adjusted to support the trimmer head at different angles and elevations when the main pole is held and said wheel is rolled across a support surface.
- d. a second clamp member attached to said extension arm that enables the angular orientation of said extension arm to be adjusted relative to the main pole on the line trimmer; and,

1

e. a locking member attached to said wheel assembly enabling said wheel assembly to be selectively locked in position on said extension arm.

9. (Original) The accessory, as recited in Claim 8, wherein said first and second clamp members are formed on a rotating L-shaped bracket selectively attaching said extension arm to the main pole, said L-shaped bracket includes a first support flange that supports said first clamp member and a second support flange that supports said second clamp member, said first support flange and said second support flange being perpendicularly aligned.

10. (Original) The accessory, as recited in Claim 8, wherein said first clamp member includes an upper clamp member, a lower clamp member, a center post, a pivoting handle attached to said post, and a strap, said upper and lower clamp members including teeth that selectively engage when said upper and lower clamp members are forced together, said strap member extending through said lower clamp member and wrapped around a main pole on a line trimmer, said center post extending through said upper clamp member and connecting to said strap to connect said upper clamp member and said lower clamp member together and to tighten said strap around the main pole.

18

11. (Original) The accessory, as recited in Claim 9, wherein said first clamp member includes an upper clamp member, a lower clamp member, a center post, a pivoting handle attached to said post, and a strap, said upper and lower clamp members including teeth that selectively engage when said upper and lower clamp members are forced together, said strap member extending through said lower clamp member and wrapped around a main pole on a

1	line trimmer, said center post extending through said upper clamp member and connecting to
2	said strap to connect said upper clamp member and said lower clamp member together and to
3	tighten said strap around the main pole.
4	
5	12. (Original) The accessory, as recited in Claim 8, wherein said wheel is rotatably mounted
6	on said wheel assembly.
7	
8	13. (Original) The accessory, as recited in Claim 8, wherein said wheel assembly is fixed in
9	position on said extension pole.
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	